



# PowerG D/W Contact w/ Aux Input

PGx945



## Visible Link Quality Indicator

Built-in LED indicator helps installers find the optimal mounting location without needing to check the keypad.



## Fully Supervised

Ensures the device is always connected and functioning properly, enhancing overall reliability.



## Configurable Aux Input

Normally Open, Normally Closed, or Single End-of-Line configuration.



## Long Battery Life

Powered by a 3V CR123A lithium battery for up to 8 years of battery life.



## PowerG Technology

Delivers secure, long-range, and reliable performance—even in challenging environments.



## Easy Configuration

All settings are managed through the system keypad for a streamlined setup and installation.



PowerG

DSC



## SPECIFICATIONS

|                            |                                                              |
|----------------------------|--------------------------------------------------------------|
| Dimensions (LxWxD)         | 81 x 34 x 25 mm (3.19 x 1.25 x 1 in)                         |
| Battery Life               | Up to 8 years (with typical usage)                           |
| Battery Type               | 3V CR123A Lithium Battery (GP, Panasonic and Duracell only)  |
| Weight (including battery) | 53 g (1.9 oz)                                                |
| Operating Temperature      | -10°C to 55°C (14°F to 131°F)                                |
| Relative Humidity          | up to max, 93 % RH, non-condensing                           |
| Approvals & Certifications | FCC/IC<br>UL/ULC<br>CSFM for residential fire applications   |
| Part Number(s)             | PG9945 - 912-919 MHz<br>PG8945 - 868 MHz<br>PG4945 - 433 MHz |



PowerG

DSC

